

The T1 GYS AUTO is a three phase MIG-MAG, with torch connector, recommended for welding steel, stainless steel, aluminium and for MIG brazing of high-tensile strength steels with CuSi and CuAl wires (ideal for car body repairs).

Synergic Mode

• The machine determines the optimum wire speed by selecting :

- the type of wire
- the wire diameter
- the welding current



Spool Gun connector

The Spool Gun torch is ideal for car body repairs of aluminium, AISi5 and AISi12.

4 Drive rolls motor

Suitable for ø200mm and ø300mm wire reels (15kg max).

Saving welding parameters

Memory save feature for each torch and activation of the 'last used' welding parameters (wire diameter, wire type & mode).

3 Welding modes available

- Standard (2T)
- Spot
- Delay




Accessories

Delivered with:
- 1 torch 150A - 3m
- 1 earth clamp 200A - 3m
(regulator not included)

Optional Spool Gun (ref.041486)

+ PRODUIT



Upgradeable - the T1 GYS AUTO can be fitted with a Spool Gun torch. This motorised torch is suitable for ø100mm wire reels of aluminium, stainless steel, copper and steel in ø0.8mm.

- Ideal for soft wire such as the AISi5 or AISi12 (recommended for car body repairs)
- Ease of use : adjusting the wire speed on the Spool Gun torch directly.

CE - EN 60974-1

50/60hz	AM	min▷max	ø mm	100	200	300	équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica	EN60974-1 (40°C)	cm/kg	Protected & compatible POWER GENERATOR (+/- 15%)	Spool Gun
400V	10A	15▷200A	0.6-1.0	✓	✓	✓	0.6 - 0.8	110A	47x77x79 55	5 kVA	Option
230/400V	16/10A							150A 25%			