

GYSPOT ARCPULL 200 is a drawn arc welding product developed specifically for thin car body sheet metal. Its innovative gun is equipped with a high precision linear motor with digital control, which provides refined synergies.

DRAWN ARC : A PROFESSIONAL PROCESS

For Aluminium Dent-Pulling, drawn arc welding has several advantages as compared to capacitor discharge technology :

- Gas protection which prevents contamination of the weld
- Deep repair capabilities
- Closer Key fitment for stronger pulling capabilities
- Reduction in post repair preparation
- Excellent Reproduction and reliability process
- No impact on the reverse side of the repaired panel.

GROUND BREAKING INNOVATION

The gun is equipped with a linear motor which is superior and unique in the market. Unprecedented advantages :

- Superior control of the welding cycle.
- Digital process control - no need for manual adjustments.
- 2 independently adjustable ground electrodes for better stability during the welding process.



• Included :

- Automatic gun with 2 Ground Electrodes
- Aluminium Keys consumables box 1,5 mm.
- Lifting rod

Ref. 057470

• Welds aluminium and steel studs:

- Steel studs up to Ø 6 mm.
- Aluminium studs up to Ø 6 mm

• SPECIAL GYSPOT ARC PULL 200

**Aluminium Keys
consumable box**
1.0 mm 059412
1.5 mm 059429



2 WELDING MODES

A digital interface provides intuitive and functional navigation between the welding modes :

- A synergic mode which provides factory pre-established programs for fast and easy settings.
- A manual mode for users who require complete control - this provides personalized settings for specific use.


		Straight pulling Keys			
		1.0 mm		1.5 mm	
x 50	Al-Special - x 100	n° 1 059535		n° 4 059559	
x 50	AlMg3 - x 100	n° 2 059498		n° 5 059511	
x 50	AlMgSi - x 100	n° 3 059450		n° 6 059474	
		Twisted pulling keys			
x 20	Al-Special - x 50	n° 1 059542		n° 4 059566	
x 20	AlMg3 - x 50	n° 2 059504		n° 5 059528	
x 20	AlMgSi - x 50	n° 3 059467		n° 6 059481	

ACCESSORIES

+ INCLUDED



+ OPTIONS



50/60hz	I ₂ MAX	APPARENT POWER (VA)	INTEGRATED TECHNOLOGY			SEPARATE CABLE GUN	U ₂ V	I RMS A	I RMS A	OK	OK	BOX : 20,5 x 25 x 33 / 11,9 48 x 27,7 x 36 / 13,8
			SYNERGIC	FV	SR							
110 V 1~ 230 V 1~	10>100 A 10>200 A	7.4kVA	•	•	•	SYNERGIC DIGITAL GUN LINEAR MOTOR	-	20,4 > 24 20,4 > 28	16	-	OK	OK