

GENESI CARBONIO 360 EVO GEO

FIELD OF APPLICATION: WATERBORNE BASE AND SOLVENT CLEAR COAT

One of the masterpiece of the Walcom® brand, the GEO dual atomization system, hvp in respect to the California norm n. 1151 SCAQMD with 0.7 bar at the air cap and more then 65% transfer efficiency, perfect for color match. The dual atomizing nozzle, 6 pre-atomizing holes, excellent product lay out, unique system that delivers incredible performance.

It's very low in air consumption 425 l/min / 15 cfm, saving air and consequently energy.

GENESI CARBONIO 360 EVO GEO is an excellent professional tool and these are some of the features:

- high atomization and product lay out for base coats,
- low air consumption 425 l/min at 2 bar / 15 cfm at 29 psi: LV technology,
- HVLP max 2 bar / 29 psi,
- certified transfer efficiency over 70%,
- integrated pressure regulator, with spray gun air inlet adjustment knob,
- quick connect/release digital pressure gauge,
- nozzle with special diffuser for airflow homogeneity,
- easy to adjust and versatility,
- carbon fiber for lightness and ergonomic design,
- excellent color match, certified by main paint companies,
- resistant to solvent and pickling chemicals,
- 340 g weight, the lightest on the market.

Walcom®
SPRAY GUN EVOLUTION

CE Ex II 2G X



Check the correct setup of the spray gun here, or visit www.walmec.com/solutionfinder



MADE IN ITALY

TECHNICAL DATA

Body: forged aluminum and carbon fiber

Handle and trigger: carbon fiber

Air cap: anodized aluminum

Air cap ring: carbon fiber

GEO nozzle: stainless steel AISI 303

Needle-springs: stainless steel AISI 303

Seal gaskets: self-lubricating PTFE (teflon)

Weight: 340 g

Operating air pressure: range 0.5 - 2.5 bar (7.2 - 36 psi) / HVLP max 2 bar (29 psi)

Air consumption: 425 l/min at 2 bar / 15 cfm at 29 psi

Ø ugello: 1.0 - 1.1 - 1.2 - 1.3 - 1.4 - 1.5 - 1.7 - 1.9

GENESI CARBONIO 360 EVO GEO

ITEM ID	COMPOSITION	PACKAGING	Recommended use
W0430**	Cup POM C 680 cc + Integrated pressure regulator and carbon fiber quick release/connection digital pressure gauge.	■	 BASE COAT
W0435**	Cup aluminum 750 cc + Integrated pressure regulator and carbon fiber quick release/connection digital pressure gauge.	■	
W0420**	Cup POM C 680 cc Integrated pressure regulator NO pressure gauge	■	Packaging
W0425**	Cup aluminum 750 cc Integrated pressure regulator NO pressure gauge	■	
W0465**	Spray gun only + Integrated pressure regulator and carbon fiber quick release/connection digital pressure gauge.	■	

Note:
add nozzle Ø to ITEM ID (**)